

Product Parameter

 Series: Xtreme-10

Weight, Power & Current are dedicated to single face sign

Sn	Product Model	Height	Width	Weight (LBS)	Power (W)	Current (A @120V)
1	Xtreme-10 32x96-SMD	1'0.6"	3'1.8"	58	287	2.4
2	Xtreme-10 32x128-SMD	1'0.6"	4'2.4"	72	374	3.1
3	Xtreme-10 32x160-SMD	1'0.6"	5'3.0"	83	461	3.8
4	Xtreme-10 32x192-SMD	1'0.6"	6'3.5"	104	562	4.7
5	Xtreme-10 32x224-SMD	1'0.6"	7'4.1"	117	649	5.4
6	Xtreme-10 32x256-SMD	1'0.6"	8'4.7"	127	736	6.1
7	Xtreme-10 32x288-SMD	1'0.6"	9'5.3"	139	823	6.9
8	Xtreme-10 32x320-SMD	1'0.6"	10'5.9"	175	924	7.7
9	Xtreme-10 32x352-SMD	1'0.6"	11'6.5"	185	1,011	8.4
10	Xtreme-10 32x384-SMD	1'0.6"	12'7.1"	196	1,098	9.2
11	Xtreme-10 64x128-SMD	2'1.2"	4'2.4"	121	736	6.1
12	Xtreme-10 64x160-SMD	2'1.2"	5'3.0"	129	910	7.6
13	Xtreme-10 64x192-SMD	2'1.2"	6'3.5"	185	1,112	9.3
14	Xtreme-10 64x224-SMD	2'1.2"	7'4.1"	205	1,286	10.7
15	Xtreme-10 64x256-SMD	2'1.2"	8'4.7"	223	1,460	12.2
16	Xtreme-10 64x288-SMD	2'1.2"	9'5.3"	250	1,634	13.6
17	Xtreme-10 64x320-SMD	2'1.2"	10'5.9"	304	1,835	15.3
18	Xtreme-10 64x352-SMD	2'1.2"	11'6.5"	322	2,009	16.7
19	Xtreme-10 64x384-SMD	2'1.2"	12'7.1"	340	2,183	18.2
20	Xtreme-10 96x128-SMD	3'1.8"	4'2.4"	165	1,098	9.2
21	Xtreme-10 96x160-SMD	3'1.8"	5'3.0"	185	1,359	11.3
22	Xtreme-10 96x192-SMD	3'1.8"	6'3.5"	258	1,661	13.8
23	Xtreme-10 96x224-SMD	3'1.8"	7'4.1"	287	1,921	16.0
24	Xtreme-10 96x256-SMD	3'1.8"	8'4.7"	312	2,183	18.2
25	Xtreme-10 96x288-SMD	3'1.8"	9'5.3"	350	2,444	20.4
26	Xtreme-10 96x320-SMD	3'1.8"	10'5.9"	422	2,746	22.9
27	Xtreme-10 96x352-SMD	3'1.8"	11'6.5"	452	3,020	25.2
28	Xtreme-10 96x384-SMD	3'1.8"	12'7.1"	478	3,281	27.3
29	Xtreme-10 128x160-SMD	4'2.4"	5'3.0"	241	1,808	15.1
30	Xtreme-10 128x192-SMD	4'2.4"	6'3.5"	332	2,211	18.4
31	Xtreme-10 128x224-SMD	4'2.4"	7'4.1"	368	2,559	21.3
32	Xtreme-10 128x256-SMD	4'2.4"	8'4.7"	401	2,907	24.2
33	Xtreme-10 128x288-SMD	4'2.4"	9'5.3"	453	3,267	27.2
34	Xtreme-10 128x320-SMD	4'2.4"	10'5.9"	546	3,670	30.6
35	Xtreme-10 128x352-SMD	4'2.4"	11'6.5"	578	4,018	33.5
36	Xtreme-10 128x384-SMD	4'2.4"	12'7.1"	610	4,366	36.4
37	Xtreme-10 160x192-SMD	5'3.0"	6'3.5"	406	2,760	23.0
38	Xtreme-10 160x224-SMD	5'3.0"	7'4.1"	455	3,207	26.7
39	Xtreme-10 160x256-SMD	5'3.0"	8'4.7"	498	3,642	30.4
40	Xtreme-10 160x288-SMD	5'3.0"	9'5.3"	563	4,077	34.0
41	Xtreme-10 160x320-SMD	5'3.0"	10'5.9"	667	4,581	38.2
42	Xtreme-10 160x352-SMD	5'3.0"	11'6.5"	712	5,028	41.9
43	Xtreme-10 160x384-SMD	5'3.0"	12'7.1"	752	5,463	45.5



Product Parameter

44	Xtreme-10 192x224-SMD	6'3.5"	7'4.1"	541	3,844	32.0
45	Xtreme-10 192x256-SMD	6'3.5"	8'4.7"	589	4,366	36.4
46	Xtreme-10 192x288-SMD	6'3.5"	9'5.3"	670	4,888	40.7
47	Xtreme-10 192x320-SMD	6'3.5"	10'5.9"	784	5,492	45.8
48	Xtreme-10 192x352-SMD	6'3.5"	11'6.5"	837	6,027	50.2
49	Xtreme-10 192x384-SMD	6'3.5"	12'7.1"	885	6,549	54.6